

Slings

Samson ► WHOOPIE SLING

The Whoopie Sling is an adjustable lifting sling with a permanent eye at one end and an adjustable eye at the other that allows it to easily adapt to a variety of tasks and loads. The adjustment allows snug lifting control and minimizes the number of fixed length slings required. The sling is a braided non-torquing polyester rope with Samthane coating. This coating provides increased sling durability. Each sling has a permanent rating tag attached.



| Sling Material | Part No. | Diameter | Length | Eye Size | Permanent Single Leg | Choker | Rated Capacity Basket |
|----------------|----------|----------|--------------|----------|----------------------|------------|-----------------------|
| Tenex | B1ABW462 | 1/2" | 2-1/2' - 4' | 5" | 2,220 lbs. | 1,760 lbs. | 4,400 lbs. |
| | B1ABW562 | 5/8" | 3' - 5' | 6" | 3,200 lbs. | 2,560 lbs. | 6,400 lbs. |
| | B1ABW662 | 3/4" | 3-1/2' - 6' | 7" | 4,200 lbs. | 3,380 lbs. | 8,400 lbs. |
| | B1AB1062 | 3/4" | 3-1/2' - 10' | 7" | 4,200 lbs. | 3,380 lbs. | 8,400 lbs. |
| | B1AB1262 | 3/4" | 3-1/2' - 12' | 7" | 4,200 lbs. | 3,380 lbs. | 8,400 lbs. |
| | B1AB1462 | 3/4" | 3-1/2' - 14' | 7" | 4,200 lbs. | 3,380 lbs. | 8,400 lbs. |

Samson ► FIXED EYE

TreeRig slings are everything that you expect from Samson: strong and tough. The Tenex version is designed for strength and better conformity to any surface while the Stable Braid is low-stretch and abrasion resistant, while still maintaining high strength.



| Sling Material | Part No. | Diameter | Length | Eye Size | Choker |
|----------------|------------|----------|--------|----------|------------|
| Tenex | B1T5810SL | 5/8" | 10' | 6" | 3,800 lbs. |
| | B1T3412SL | 3/4" | 12' | 6" | 5,000 lbs. |
| Stable Braid | B1SB5810SL | 5/8" | 10' | 6" | 3,300 lbs. |
| | B1SB3414SL | 3/4" | 14' | 6" | 4,100 lbs. |

Pelican ► FIXED EYE

Double-braid/composite construction of polyester cover over nylon core results in higher tensile strength and better shock load performance. These slings are urethane coated for abrasion resistance and have a Cordura® sleeve spliced into the eye for added sling life.



| Sling Material | Part No. | Diameter | Length | Eye Size | Choker |
|----------------|----------|----------|--------|----------|------------|
| Double Braid | B1AB120 | 5/8" | 10' | 8" | 2,900 lbs. |
| | B1AB140 | 5/8" | 12' | 8" | 2,900 lbs. |
| | B1AB160 | 5/8" | 14' | 8" | 2,900 lbs. |
| | B1AB205 | 3/4" | 16' | 8" | 4,880 lbs. |



Rigging

Weaver ► EYE AND EYE

This eye and eye web sling is great for all manner of rigging work. They are compact, lightweight, and strong. Each sling comes with its own tag indicating the safe Working Load Limit.



| Sling Material | Part No. | Diameter | Length | Eye Size | Permanent Single Leg | Choker | Rated Capacity Basket |
|----------------|----------|----------|--------|----------|----------------------|----------|-----------------------|
| Nylon Web | B1ABSL30 | 1" | 30" | 3" | 1,200 lbs. | 960 lbs. | 2,400 lbs. |
| | B1ABSL40 | 1" | 40" | 3" | 1,200 lbs. | 960 lbs. | 2,400 lbs. |
| | B1ABSL62 | 1" | 62" | 3" | 1,200 lbs. | 960 lbs. | 2,400 lbs. |

Rigging

CMI Stainless Steel Rigging Blocks

These blocks were designed by CMI specifically for use in false crotch systems to help save wear and tear on bull ropes. The upper bushing maximizes sling strength and wide sideplates protect the rope from contact with rough bark. Convenient milled knobs allow for easy rigging of the upper bushing. Fabricated from stainless steel and aluminum for lasting durability in outdoor conditions.



| 5/8" Stainless Steel Block | | | | |
|----------------------------|----------|------------|-----------|----------|
| | Capacity | Tensile | WLL | Weight |
| B1ABRP130 | 5/8" | 28000 lbs. | 2800 lbs. | 2.3 lbs. |

| 3/4" Stainless Steel Block | | | | |
|----------------------------|----------|------------|-----------|----------|
| | Capacity | Tensile | WLL | Weight |
| B1ABRP131 | 3/4" | 40000 lbs. | 4000 lbs. | 5.6 lbs. |

False Crotch Block and Sling

This combination comes with a 16' x 3/4" double-braided rigging sling with Cordura® collar and steel block for 4,880 lbs. of rigging capability.

B1AB125



ISC Aluminum Rigging Blocks

These rigging blocks from ISC combine the convenience of a spring loaded upper pin with a captive bushing, and a lightweight aluminum design. Simply push and twist the upper pin, and the cheekplates will swing open. Best of all, the bushing and pin can not fall out of the block. The sheave and bushing pins are stainless steel.



| 5/8" Aluminum Block | | | | |
|---------------------|----------|------------|-----------|----------|
| | Capacity | Tensile | WLL | Weight |
| B1AB5007S | 5/8" | 22000 lbs. | 4400 lbs. | 3.5 lbs. |

| 3/4" Aluminum Block | | | | |
|---------------------|----------|------------|-----------|----------|
| | Capacity | Tensile | WLL | Weight |
| B1AB5007L | 3/4" | 33000 lbs. | 6600 lbs. | 5.1 lbs. |

Rigging Plate

This lightweight aluminum rigging plate allows expert arborists to create multiple anchor systems and advanced rigging systems while maintaining easy organization. Even though it is lightweight, it is incredibly strong with a tensile strength of over 6,700 lbs. (30 kN).

B1AB8645





Slings and Runners

Petzl Anchor Straps

This device can be used as either an anchor strap or a sling for lifting heavy loads. Made of high-strength webbing, that is resistant to abrasion. It is 1-3/4" wide and has a forged steel D-rings at each end for 7,800 lbs. of strength.

| Petzl Anchor Strap | |
|--------------------|-----|
| B1ABC42100 | 40" |
| B1ABC42150 | 60" |
| B1ABC42200 | 80" |

CMI Sewn Runners

CMI doesn't make any wild claims about their sewn runners. They simply use the best material and have incredibly strong bar-tacks. All that matters is that your bar-tacks are stronger than your webbing and CMI's are strong enough to withstand up to an amazing 6,800 lbs. All runners are 1" wide.



| CMI Sewn Runners | |
|------------------|-----|
| B1ABAAS26 | 26" |
| B1ABAAS30 | 30" |
| B1ABAAS36 | 36" |
| B1ABAAS40 | 40" |
| B1ABAAS42 | 42" |
| B1ABAAS48 | 48" |



CMI Daisy Chain

CMI's daisy chain can be used to haul numerous items into the canopy. End-to-end strength is an incredible 6,800 lbs. while individual loops are rated to 2,900 lbs.

B1ABDC001



Port-A-Wrap III

The Port-A-Wrap is the strongest, easiest friction lowering device on the market. Commonly used with one of our Whoopie slings, this device can lower even the heaviest of trees safely and easily to the ground. The wide diameter of the centerpiece creates more surface area for your rope creating even more friction with fewer wraps. In addition, this design decreases the bend in your line increasing the lifespan of your line. The Port-A-Wrap is heavy-duty steel and comes in two sizes accommodating rope up to 3/4" in diameter. Safe working load of up to 2,000 lbs.

For ropes up to 9/16"

B1AB6011

For ropes up to 3/4"

B1AB601L



Rescue 8

With a tensile strength of over 11,000 lbs., our steel Rescue 8 is perfect for light-duty rigging while working in the canopy. It is easy to install and lighter than the Port-A-Wrap.

B1AB462



Maasdam Pow'R-Pull®

With more than 50 years of experience making pullers, Maasdam produces one of the best there is.

- 3/4 ton capacity
- Aluminum alloy ratchet wheel
- High-strength electro-plated steel parts
- "Notch-at-a-time" letdown
- Drop forged steel hook
- Uses 1/2" 3-strand twisted rope (rope not included)

B1ABAO



Rigging